



ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY (ASISTENCIA AL PEDALEO)	
MOTOR	SyncDriveMove Plus Hub drive 75Nm max
MANDO	Mode support switch from SRAM Blips
PANTALLA	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATERÍA	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CARGADOR	Giant EnergyPak 4A smart charger, 60% in 1:45
CONECTIVIDAD	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CUADRO	
TALLAS	XS, S, M, L
COLORES	Golden Haze / Carbon smoke
CUADRO	Advanced-grade composite,12x145 thru-axle
HORQUILLA	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
AMORTIGUADOR	-
COMPONENTES	
MANILLAR	Liv Contact SL D-Fuse 31.8 alloy
POTENCIA	Contact SL Aerolight 31.8 alloy
TIJA DE SILLÍN	Giant D-Fuse, Composite, 14mm offset
SILLÍN	Liv Approach
PEDALES	-
TRANSMISIÓN	
MANETAS DE CAMBIO	Sram Rival eTap AXS
DESVIADOR	Sram Rival eTap AXS
CAMBIO TRASERO	Sram Rival eTap AXS
FRENOS	Sram Rival eTap HRD, Paceline 160mm center-lock [F] 160mm 6-bols [R]
PALANCAS DE FRENOS	Sram Rival eTap AXS HRD
CASSETTE	Sram Rival XG-1250 10x36T 12-speed
CADENA	Sram Rival 12-speed
JGO. PLATOS Y BIELAS	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E crank Alloy ISIS
CAJA DE PEDALIER	Giant E+ System BBSS

RUEDAS	
LLANTAS	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle
RADIOS	Sapim spoke E-Light [R] Race [F], e-bike optimized
CUBIERTAS	Giant Gavia Fondo 0 700x32C 170TPI Tubeless Foldable
EXTRAS	Fender adapter
ACCESORIOS	
LUCES	Seatpost clamp integrated tail light

Precio: 6.499,00 €

GEOMETRÍA

CUADRO	XS	S	M
Longitud del tubo del sillín (mm)	400	435	470
Ángulo del tubo del sillín	74,5°	74,5°	74,0°
Longitud del tubo superior (mm) (mm)	515	525	540
Longitud del tubo de dirección (mm) (mm)	120	135	155
Ángulo del tubo de dirección	70,5°	71,0°	72,0°
Inclinación de la horquilla (mm)	50	50	50
Trail (mm) (mm)	72	68,3	61,8
Distancia entre ejes (mm) (mm)	993	999,2	1003
Longitud de la vaina (mm) (mm)	420	420	420
Caída del eje de pedalier (mm) (mm)	80	80	80
Stack (mm) (mm)	528,9	545	562,8
Reach (mm) (mm)	368	373,6	378,4
Altura del suelo al tubo (mm) (mm)	677	708	743
Ancho del manillar (mm) (mm)	380	400	400
Longitud de la potencia (mm) (mm)	80	90	100
Longitud de las bielas (mm) (mm)	165	165	170
Tamaño de ruedas	700C	700C	700C

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.